



SPR Press Tie

ENGLISH



Reliable, Ergonomic.



STRONGER TOGETHER

TIPPER TIE™

SPR Press Tie

Area of Application

The Signature Series SPR Press Tie is ideal for low-cost packaging of pressure-packed products with uniform density or circumference. The Press Tie is the easiest and most reliable way to pack portion-controlled items such as Canadian bacon, smoked butts, rolled and flattened hams, and rolls of all kinds.

Technology & Function

The SPR Press Tie bench clipper is capable of handling all types of casings including fibrous and coated fibrous, as well as nylon and poly stockinette. The SPR features an adjustable air pressure control that permits the casing pulling cylinder to operate at any pre-set air pressure. Each model is constructed from stainless steel and other non-corrosive materials, meeting sanitary design requirements.

The SPR is easy to use, applying a secure seal with one quick, continuous motion. This hand-operated clipper gathers, draws the product tight and then clips the package.

Technical Specifications

Dimensions (L x W x H):	37.9 x 15.9 x 28.5 (962 x 403,9 x 723,9 mm)
Weight:	60 lbs (27,2 kg)
Air Consumption	.3 CFM per cycle @ 80 PSI (8,5 liters at 5,5 bar)
Clip type, SPR463:	410K and 411K
Clip type, SPR465:	400G, 401G, 401T, 451T


Vertically mounted and pneumatically operated, it is available in several clip sizes to suit the product.

Advantages

- Low lifecycle costs due to robust design
- Minimal service and maintenance costs
- High stability with simultaneous loading of a very small production area
- Hygienic design, smooth surfaces, stainless steel materials
- The high closure speed supports the ergonomic workflow of the operator
- Precise control over clip closure pressure

Equipment versions

- A knife ensures straight ends with a good appearance
- The FRL assembly (filter/regulator/lubricator) provides clean operating air at the right pressure, reducing maintenance costs.



Gate allows easy entry of product and superior voiding of casing or netting material.



Adjustable air pressure gauge provides optimum package tightness.



Ergonomic design eliminates worker strain via a knurled cylinder clamp that firmly grips casing to pull product.

TIPPER TIE, Inc.
2000 Luffkin Road
Apex, NC 27539 USA
Tel. +1 919 362 8811
Fax +1 919 362 4839
infoUS@tippertie.com

TIPPER TIE TECHNOPACK GmbH
Wilhelm-Bergner-Strasse 9a
21509 Glinde/Germany
Tel. +49 40 72 77 04 0
Fax +49 40 72 77 04 100
infoDE@tippertie.com

